



Beverage Run Rise Charts

FOR T5000 AND G55 PUMPS

FLOJET

a xylem brand

G55 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 0 | 51 | 53 | 57 | 61 | 65 | 70 | 74 | 82 | 90 | | | | | |
| | 50 | 51 | 52 | 54 | 55 | 57 | 58 | 61 | 64 | 67 | 70 | 73 | 76 | 80 |
| 10 | 56 | 58 | 62 | 66 | 70 | 75 | 79 | 87 | | | | | | |
| | 55 | 56 | 57 | 59 | 60 | 62 | 63 | 66 | 69 | 72 | 75 | 78 | 81 | 85 |
| 20 | 61 | 63 | 67 | 71 | 75 | 80 | 84 | | | | | | | |
| | 60 | 61 | 62 | 64 | 65 | 67 | 68 | 71 | 74 | 77 | 80 | 83 | 86 | 90 |
| 30 | | 68 | 72 | 76 | 80 | 85 | 89 | | | | | | | |
| | | 66 | 67 | 69 | 70 | 72 | 73 | 76 | 79 | 82 | 85 | 88 | | |
| 40 | | 73 | 77 | 81 | 85 | 90 | | | | | | | | |
| | | 71 | 72 | 74 | 75 | 77 | 78 | 81 | 84 | 87 | 90 | | | |
| 50 | | 78 | 82 | 86 | 90 | | | | | | | | | |
| | | 76 | 77 | 79 | 80 | 82 | 83 | 86 | 89 | | | | | |
| 60 | | | 87 | | | | | | | | | | | |
| | | | 82 | 84 | 85 | 87 | 88 | | | | | | | |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895

G55 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 0 | 49 | 51 | 53 | 56 | 58 | 61 | 64 | 66 | 69 | 74 | 79 | 84 | 90 | | |
| 10 | 48 | 49 | 49 | 50 | 50 | 51 | 51 | 52 | 53 | 54 | 55 | 56 | 57 | 58 | 60 |
| 20 | 53 | 54 | 54 | 55 | 55 | 56 | 56 | 57 | 58 | 59 | 60 | 61 | 62 | 63 | 65 |
| 30 | 58 | 59 | 59 | 60 | 60 | 61 | 61 | 62 | 63 | 64 | 65 | 66 | 67 | 68 | 70 |
| 40 | 66 | 68 | 71 | 73 | 76 | 79 | 81 | 84 | 89 | | | | | | |
| 50 | 64 | 64 | 65 | 65 | 66 | 66 | 67 | 68 | 69 | 70 | 71 | 72 | 73 | 75 | |
| 60 | 71 | 73 | 76 | 78 | 81 | 84 | 86 | 89 | | | | | | | |
| | 69 | 69 | 70 | 70 | 71 | 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 80 | |
| | 76 | 78 | 81 | 83 | 86 | 89 | | | | | | | | | |
| | 74 | 74 | 75 | 75 | 76 | 76 | 77 | 78 | 79 | 80 | 81 | 82 | 83 | 85 | |
| | | 83 | 86 | 88 | | | | | | | | | | | |
| | | 79 | 80 | 80 | 81 | 81 | 82 | 83 | 84 | 85 | 86 | 87 | 88 | 90 | |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895

G55 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 0 | 52 | 54 | 60 | 65 | 70 | 76 | 81 | | | | | | | |
| 10 | 50 | 57 | 59 | 55 | 56 | 58 | 60 | 64 | 68 | 71 | 75 | 79 | 82 | 86 |
| 20 | 57 | 59 | 65 | 70 | 75 | 81 | 86 | | | | | | | |
| 30 | 55 | 56 | 58 | 60 | 61 | 63 | 65 | 69 | 73 | 76 | 80 | 84 | 87 | |
| 40 | 62 | 64 | 70 | 75 | 80 | 86 | | | | | | | | |
| 50 | 60 | 61 | 63 | 65 | 66 | 63 | 70 | 74 | 78 | 81 | 85 | 89 | | |
| 60 | | 69 | 75 | 80 | 85 | | | | | | | | | |
| | | 66 | 68 | 70 | 71 | 73 | 75 | 79 | 83 | 86 | 90 | | | |
| | | 74 | 80 | 85 | 90 | | | | | | | | | |
| | | 71 | 73 | 75 | 76 | 78 | 80 | 84 | 88 | | | | | |
| | | 79 | 85 | 90 | | | | | | | | | | |
| | | 76 | 78 | 80 | 81 | 83 | 85 | 89 | | | | | | |
| | | | 90 | | | | | | | | | | | |
| | | | 83 | 85 | 86 | 88 | 90 | | | | | | | |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895

G55 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 0 | 50 | 52 | 55 | 59 | 63 | 67 | 70 | 78 | 85 | | | | | |
| | 49 | 49 | 50 | 52 | 53 | 54 | 55 | 58 | 60 | 62 | 65 | 67 | 70 | 72 |
| 10 | 55 | 57 | 60 | 64 | 68 | 72 | 75 | 83 | 90 | | | | | |
| | 54 | 54 | 55 | 57 | 58 | 59 | 60 | 63 | 65 | 67 | 70 | 72 | 75 | 77 |
| 20 | 60 | 62 | 65 | 69 | 73 | 77 | 80 | 88 | | | | | | |
| | 59 | 59 | 60 | 62 | 63 | 64 | 65 | 68 | 70 | 72 | 75 | 77 | 80 | 82 |
| 30 | | 67 | 70 | 74 | 78 | 82 | 85 | | | | | | | |
| | | 64 | 65 | 67 | 68 | 69 | 70 | 73 | 75 | 77 | 80 | 82 | 85 | 87 |
| 40 | | 72 | 75 | 79 | 83 | 87 | 90 | | | | | | | |
| | | 69 | 70 | 72 | 73 | 74 | 75 | 78 | 80 | 82 | 85 | 87 | 90 | |
| 50 | | 77 | 80 | 84 | 88 | | | | | | | | | |
| | | 74 | 75 | 77 | 78 | 79 | 80 | 83 | 85 | 87 | 90 | | | |
| 60 | | | 85 | 89 | | | | | | | | | | |
| | | | 80 | 82 | 83 | 84 | 85 | 88 | 90 | | | | | |

Conversions:
Feet to Meters:
 Multiply by .3048
PSI to BAR:
 Multiply by .06895

T5000 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 | 800 | 900 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 0 | 54 | 56 | 60 | 64 | 68 | 73 | 77 | | | | | | |
| 10 | 53 | 54 | 55 | 57 | 58 | 60 | 61 | 64 | 67 | 70 | 73 | 76 | 79 |
| 20 | 59 | 61 | 65 | 69 | 73 | 78 | | | | | | | |
| 30 | 58 | 59 | 60 | 62 | 63 | 65 | 66 | 69 | 72 | 75 | 78 | | |
| 40 | 64 | 66 | 70 | 74 | 78 | | | | | | | | |
| 50 | 63 | 64 | 65 | 67 | 68 | 70 | 71 | 74 | 77 | 80 | | | |
| | | 71 | 75 | 79 | | | | | | | | | |
| | | 69 | 70 | 72 | 73 | 75 | 76 | 79 | | | | | |
| | | 76 | 80 | | | | | | | | | | |
| | | 74 | 75 | 77 | 78 | 80 | | | | | | | |
| | | | | | | | | | | | | | |
| | | 79 | 80 | | | | | | | | | | |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895

T5000 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 0 | 51 | 53 | 55 | 58 | 60 | 63 | 66 | 71 | 76 | | | | | |
| 10 | 50 | 51 | 51 | 52 | 52 | 53 | 53 | 55 | 56 | 57 | 58 | 59 | 60 | 62 |
| 20 | 56 | 58 | 60 | 63 | 65 | 68 | 71 | 76 | | | | | | |
| 30 | 61 | 63 | 65 | 68 | 70 | 73 | 76 | | | | | | | |
| 40 | 60 | 61 | 61 | 62 | 62 | 63 | 63 | 65 | 66 | 67 | 68 | 69 | 70 | 72 |
| 50 | | 68 | 70 | 73 | 75 | 78 | | | | | | | | |
| | | 66 | 66 | 67 | 67 | 68 | 68 | 70 | 71 | 72 | 73 | 74 | 75 | |
| | | 73 | 75 | 78 | 80 | | | | | | | | | |
| | | 71 | 71 | 72 | 72 | 73 | 73 | 75 | 76 | 77 | 78 | 79 | | |
| | | 78 | 80 | | | | | | | | | | | |
| | | 76 | 76 | 77 | 77 | 78 | 78 | 80 | | | | | | |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895

T5000 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 0 | 55 | 57 | 63 | 68 | 73 | 79 | | | | | |
| | 53 | 54 | 56 | 58 | 59 | 61 | 63 | 67 | 71 | 74 | 78 |
| 10 | 60 | 62 | 68 | 73 | 78 | | | | | | |
| | 58 | 59 | 61 | 63 | 64 | 66 | 68 | 72 | 76 | 79 | |
| 20 | 65 | 67 | 73 | 78 | | | | | | | |
| | 63 | 64 | 66 | 68 | 69 | 71 | 76 | 77 | | | |
| 30 | | 72 | 78 | | | | | | | | |
| | | 69 | 71 | 76 | 74 | 76 | 78 | | | | |
| 40 | | 77 | | | | | | | | | |
| | | 74 | 76 | 78 | 79 | | | | | | |
| 50 | | | | | | | | | | | |
| | | | | | | | | | | | 79 |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895

T5000 Series Pumps - Run/Rise Charts

CO₂ Regulator Settings for B-I-B Pump Installation

Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

| | |
|---|---------------------------|
| A | < Reading for 3/8" tubing |
| B | < Reading for 1/2" tubing |

One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

| | 25 | 50 | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 0 | 52 | 54 | 57 | 61 | 65 | 69 | 72 | 80 | | | | | | |
| 10 | 51 | 51 | 52 | 54 | 55 | 56 | 57 | 60 | 62 | 64 | 67 | 69 | 72 | 74 |
| 20 | 57 | 59 | 62 | 66 | 70 | 74 | 77 | | | | | | | |
| 30 | 56 | 56 | 57 | 59 | 60 | 61 | 62 | 65 | 67 | 69 | 72 | 74 | 77 | 79 |
| 40 | 62 | 64 | 67 | 71 | 75 | 79 | | | | | | | | |
| 50 | 61 | 61 | 62 | 64 | 65 | 66 | 67 | 70 | 72 | 74 | 77 | 79 | | |
| | | 69 | 72 | 76 | 80 | | | | | | | | | |
| | | 66 | 67 | 69 | 70 | 71 | 72 | 75 | 77 | 79 | | | | |
| | | 74 | 77 | | | | | | | | | | | |
| | | 71 | 72 | 74 | 75 | 76 | 77 | 80 | | | | | | |
| | | 79 | | | | | | | | | | | | |
| | | 76 | 77 | 79 | 80 | | | | | | | | | |

Conversions:

Feet to Meters:

Multiply by .3048

PSI to BAR:

Multiply by .06895



Xylem

17942 Cowan

Irvine, CA 92614

Tel +1.949.608.3900

Fax +1.949.609.3887

www.xylemflowcontrol.com

Flojet is a trademark of Xylem Inc. or one of its subsidiaries.

© 2012 Xylem, Inc. 950-0616 Rev B. 1/12