

IFQ1-S SYSTEM



10.4" H x 6" W x 4" D
(264 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

IFQ1 SYSTEM



15" H x 6" W x 4" D
(381 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

IFQ2 SYSTEM



16" H x 10" W x 7.125" D
(406 mm x 254 mm x 181 mm)

Dual Cartridge with a Quick Disconnect

IFQ1-XL SYSTEM



21" H x 6" W x 4" D
(533 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

IFQ2-XL SYSTEM



23.21" H x 13" W x 4.65" D
(590 mm x 330 mm x 118 mm)

Dual Cartridge with a Quick Disconnect

IF14C & IF18C SYSTEMS



11.75" H x 2.75" W
(279 mm x 57 mm)

Filter supplied with 1/4" or 3/8" (6 or 8 mm) compression

REPLACEMENT FILTER CARTRIDGES



IOMQ-S IOMQ

ICE MAKING CAPACITY: Up to 600 lbs. (272 kg)
Ideal for limited-space and undercounter applications

Snapshot

IFQ Series water treatment systems reduce sediment down to 1/2 micron and reduce chlorine, taste and odor at a flow rate of up to 3.0. The systems include IsoNet®, which delivers consistent protection against the precipitation and accumulation of scale and provides a protective barrier to help guard against corrosion.

Features and Benefits

- Reduces maintenance frequency and cost, and extends equipment life.
- Improves equipment operating efficiency
- Incorporates IsoNet – patented scale-inhibiting technology.
- Gradient-density depth filtration reduces dirt, rust and other debris as small as 1/2 micron to ensure clean, clear ice and protect solenoids, valves and other fittings against wear and plugging.
- High-capacity activated carbon filtration reduces taste and odor and protects equipment against corrosive chlorine.
- 1/4 turn QT "Quick-Twist" cartridge makes changing the filter quick, easy and sanitary.
- Wall-mount bracket and full-flow inlet shut-off valve make installation simple.
- Certifies to NSF Standard 42

All filter systems include:

Filter cartridge with FDA approved scale inhibitor, inlet shut-off valve, gauge and quick-connect fittings.

IOMQ replacement cartridges for use with IFQ1 & IFQ2 manifold filter systems. IOMQ-XL replacement cartridge for use with IFQ1-XL manifold filter system.

| IFQ SERIES FILTER SYSTEM | | | | | | | |
|--------------------------|---------------|-------------------------------------|---------------------|---------------------------------------|-----------------------------------|---------------|-------------------------------------|
| Model Number | Description | Service Flow Rate Max. gpm (lpm) | Capacity Gal (L) | Operating Pressure Range Psi (bar) | Inlet Water Temp Range °F (°C) | Micron Rating | Approx. Shipping Weight lbs (kg) |
| IFQ1-S | Single Filter | .75 (2.84) | 6,000 (22,712) | 10 - 125 (0.7 - 8.6) | 35 - 100 (1.7 - 38) | .5 | 2 (.91) |
| IFQ1 | Single Filter | 1.5 (5.68) | 15,000 (56,775) | | | | 3 (1.3) |
| IFQ1-XL | Single Filter | 2.25 (8.5) | 22,500 (85,162) | | | | 5 (2.3) |
| IFQ2 | Dual Filter | 3.0 (11.4) | 30,000 (113,550) | | | | 7 (3.2) |
| IFQ2-XL | Dual Filter | 4.5 (17) | 45,000 (170,344) | | | | 9 (4.1) |

| SINGLE INLINE FILTER CARTRIDGES | | | | | | |
|---------------------------------|--|-------------------------------------|---------------------------------------|-----------------------------------|---------------|-------------------------------------|
| Model Number | Description | Service Flow Rate Max. gpm (lpm) | Operating Pressure Range Psi (bar) | Inlet Water Temp Range °F (°C) | Micron Rating | Approx. Shipping Weight lbs (kg) |
| IF14C | Single Inline Cartridge 1/4" (6.35mm) compression | 1.0 (3.79) | 10 - 100 (.07 - 6.9) | 35 - 100 (2 - 38) | 10 | 2 (1) |
| IF18C | Single Inline Cartridge 3/8" (9.53mm) compression | | | | | |

| WATER FILTERS | | | | | | | |
|---------------|-----------------------------|--------|------|---------|------|---------|----------------|
| | | IFQ1-S | IFQ1 | IFQ1-XL | IFQ2 | IFQ2-XL | IF14C IF18C |
| CUBE ICE | ICEU070 | X | | | | | X |
| | ICEU150 - ICEU220 - ICEU300 | X | | | | | X |
| | CIMO320 - CIMO430 | | X | | | | |
| | CIMO520 - CIMO630 | | | X | | | |
| | CIMO826 - CIM1136 | | | | X | | |
| | CIM1446 - CIM1545 | | | | X | | |
| | CIM1845 - CIM2046 | | | | | X | |
| | ICE1506 - MODULAR | | | | X | | |
| FLAKE ICE | UCGO60 - UCG130* | X | | | | | X |
| | MFI0500 | X | | | | | X |
| | MFI0800 - MFI1256 | | | X | | | |
| | MFI1506 | | | | X | | |
| PEARL ICE | MFI2306 | | | | | X | |
| | GEMU090 | X | | | | | X |
| | GEMO450 - GEMO650 | | X | | | | |
| | GEMO956 | | | X | | | |
| | GEM1306 | | | | X | | |
| | GEM2006 | | | | | X | |

* Gourmet Ice

Installation Tips

- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for cartridge removal and replacement.
- Connect filtered water line to ice connections only. Do not use for condenser water.
- No activation procedure or flushing is required for system to perform as specified.

Extended Warranty Program

- Buy a new Ice-O-Matic Water Filter System with a new CIM Series™ Cube ice maker, replace the filter cartridge every 6 months, and Ice-O-Matic will extend the limited cuber evaporator warranty to 7 years parts and labor (U.S. and Canada only).
- New ice maker and filter must be installed at the same time.
- Ice maker and water filter must be registered with Ice-O-Matic within 10 days of installation. Register ice maker and filter at Iceomatic.com/warranty.
- Water filters must be changed every 180 days (6 months), at a minimum. All changes must be registered with Ice-O-Matic and include the water filter's model and serial numbers. Register water filter changes at www.iceomatic.com.
- Program is available with all Ice-O-Matic IFQ1-S, IFQ1, IFQ1-XL, IFQ2, IFQ2-XL, IF14C or IF18C water filter systems.
- Replacement filter must be Ice-O-Matic models.