

**IFQ1-S SYSTEM**



10.4" H x 6" W x 4" D  
(264 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

**IFQ1 SYSTEM**



15" H x 6" W x 4" D  
(381 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

**IFQ2 SYSTEM**



16" H x 10" W x 7.125" D  
(406 mm x 254 mm x 181 mm)

Dual Cartridge with a Quick Disconnect

**IFQ1-XL SYSTEM**



21" H x 6" W x 4" D  
(533 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

**IFQ2-XL SYSTEM**



23.21" H x 13" W x 4.65" D  
(590 mm x 330 mm x 118 mm)

Dual Cartridge with a Quick Disconnect

**IF14C & IF18C SYSTEMS**



11.75" H x 2.75" W  
(279 mm x 57 mm)

Filter supplied with 1/4" or 3/8" (6 or 8 mm) compression

**REPLACEMENT FILTER CARTRIDGES**



IOMQ-S IOMQ

**ICE MAKING CAPACITY:** Up to 600 lbs. (272 kg)  
Ideal for limited-space and undercounter applications

**Snapshot**

IFQ Series water treatment systems reduce sediment down to 1/2 micron and reduce chlorine, taste and odor at a flow rate of up to 3.0. The systems include IsoNet®, which delivers consistent protection against the precipitation and accumulation of scale and provides a protective barrier to help guard against corrosion.

**Features and Benefits**

- Reduces maintenance frequency and cost, and extends equipment life.
- Improves equipment operating efficiency
- Incorporates IsoNet – patented scale-inhibiting technology.
- Gradient-density depth filtration reduces dirt, rust and other debris as small as 1/2 micron to ensure clean, clear ice and protect solenoids, valves and other fittings against wear and plugging.
- High-capacity activated carbon filtration reduces taste and odor and protects equipment against corrosive chlorine.
- 1/4 turn QT "Quick-Twist" cartridge makes changing the filter quick, easy and sanitary.
- Wall-mount bracket and full-flow inlet shut-off valve make installation simple.
- Certifies to NSF Standard 42

**All filter systems include:**

Filter cartridge with FDA approved scale inhibitor, inlet shut-off valve, gauge and quick-connect fittings.

IOMQ replacement cartridges for use with IFQ1 & IFQ2 manifold filter systems. IOMQ-XL replacement cartridge for use with IFQ1-XL manifold filter system.

| IFQ SERIES FILTER SYSTEM |               |                                     |                     |                                       |                                   |               |                                     |
|--------------------------|---------------|-------------------------------------|---------------------|---------------------------------------|-----------------------------------|---------------|-------------------------------------|
| Model Number             | Description   | Service Flow Rate<br>Max. gpm (lpm) | Capacity<br>Gal (L) | Operating Pressure Range<br>Psi (bar) | Inlet Water Temp Range<br>°F (°C) | Micron Rating | Approx. Shipping Weight<br>lbs (kg) |
| IFQ1-S                   | Single Filter | .75 (2.84)                          | 6,000 (22,712)      | 10 - 125 (0.7 - 8.6)                  | 35 - 100 (1.7 - 38)               | .5            | 2 (.91)                             |
| IFQ1                     | Single Filter | 1.5 (5.68)                          | 15,000 (56,775)     |                                       |                                   |               | 3 (1.3)                             |
| IFQ1-XL                  | Single Filter | 2.25 (8.5)                          | 22,500 (85,162)     |                                       |                                   |               | 5 (2.3)                             |
| IFQ2                     | Dual Filter   | 3.0 (11.4)                          | 30,000 (113,550)    |                                       |                                   |               | 7 (3.2)                             |
| IFQ2-XL                  | Dual Filter   | 4.5 (17)                            | 45,000 (170,344)    |                                       |                                   |               | 9 (4.1)                             |

| SINGLE INLINE FILTER CARTRIDGES |  |                                     |                                       |                                   |               |                                     |
|---------------------------------|--|-------------------------------------|---------------------------------------|-----------------------------------|---------------|-------------------------------------|
| Model Number                    | Description  | Service Flow Rate<br>Max. gpm (lpm) | Operating Pressure Range<br>Psi (bar) | Inlet Water Temp Range<br>°F (°C) | Micron Rating | Approx. Shipping Weight<br>lbs (kg) |
| IF14C                           | Single Inline Cartridge 1/4"<br>(6.35mm) compression | 1.0 (3.79)                          | 10 - 100 (.07 - 6.9)                  | 35 - 100 (2 - 38)                 | 10            | 2 (1)                               |
| IF18C                           | Single Inline Cartridge 3/8"<br>(9.53mm) compression |                                     |                                       |                                   |               |                                     |

| WATER FILTERS |                             |        |      |         |      |         |                |
|---------------|-----------------------------|--------|------|---------|------|---------|----------------|
|               |                             | IFQ1-S | IFQ1 | IFQ1-XL | IFQ2 | IFQ2-XL | IF14C<br>IF18C |
| CUBE ICE      | ICEU070                     | X      |      |         |      |         | X              |
|               | ICEU150 - ICEU220 - ICEU300 | X      |      |         |      |         | X              |
|               | CIMO320 - CIMO430           |        | X    |         |      |         |                |
|               | CIMO520 - CIMO630           |        |      | X       |      |         |                |
|               | CIMO826 - CIM1136           |        |      |         | X    |         |                |
|               | CIM1446 - CIM1545           |        |      |         | X    |         |                |
|               | CIM1845 - CIM2046           |        |      |         |      | X       |                |
|               | ICE1506 - MODULAR           |        |      |         | X    |         |                |
| FLAKE ICE     | UCGO60 - UCG130*            | X      |      |         |      |         | X              |
|               | MFI0500                     | X      |      |         |      |         | X              |
|               | MFI0800 - MFI1256           |        |      | X       |      |         |                |
|               | MFI1506                     |        |      |         | X    |         |                |
| PEARL ICE     | MFI2306                     |        |      |         |      | X       |                |
|               | GEMU090                     | X      |      |         |      |         | X              |
|               | GEMO450 - GEMO650           |        | X    |         |      |         |                |
|               | GEMO956                     |        |      | X       |      |         |                |
|               | GEM1306                     |        |      |         | X    |         |                |
|               | GEM2006                     |        |      |         |      | X       |                |

\* Gourmet Ice

## Installation Tips

- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for cartridge removal and replacement.
- Connect filtered water line to ice connections only. Do not use for condenser water.
- No activation procedure or flushing is required for system to perform as specified.

## Extended Warranty Program

- Buy a new Ice-O-Matic Water Filter System with a new CIM Series™ Cube ice maker, replace the filter cartridge every 6 months, and Ice-O-Matic will extend the limited cuber evaporator warranty to 7 years parts and labor (U.S. and Canada only).
- New ice maker and filter must be installed at the same time.
- Ice maker and water filter must be registered with Ice-O-Matic within 10 days of installation. Register ice maker and filter at [Iceomatic.com/warranty](http://Iceomatic.com/warranty).
- Water filters must be changed every 180 days (6 months), at a minimum. All changes must be registered with Ice-O-Matic and include the water filter's model and serial numbers. Register water filter changes at [www.iceomatic.com](http://www.iceomatic.com).
- Program is available with all Ice-O-Matic IFQ1-S, IFQ1, IFQ1-XL, IFQ2, IFQ2-XL, IF14C or IF18C water filter systems.
- Replacement filter must be Ice-O-Matic models.