

SHURFLO® GENERAL BEVERAGE LVPO FILTRATION SYSTEMS

Shurflo LVPO filters feature the revolutionary Fibredyne™ filtration technology, and include a unique set of plumbing and mounting accessories.



LVPO-F2 Kit

SYSTEM	MICRON RATING	PART NO	DESCRIPTION	FLOW RATE		RATED CAPACITY		PACK SIZE	SHIP WT		LIST PRICE
				GPM	LPM	GALLONS	LITRES		LBS	KGS	
LVPO-F1*	5.0	94-751-00	Removes chlorine, T&O	3.00	11.36	6,000	22,710	1	3.0	1.4	\$160.00
LVPO-F2	5.0	94-479-00	Removes sediment and scale	3.00	11.36	—	—	1	3.0	1.4	175.00
LVPO-F3*	5.0	94-751-01	Removes chlorine, T&O and scale	3.00	11.36	6,000	22,710	1	3.0	1.4	197.00
LVPO-F4*	—	94-751-02	Hardness removal	0.50	1.89	250	946	1	4.0	1.8	242.00

SHURFLO LVPO REPLACEMENT CARTRIDGES



LVPO-F1

LVPO-F2

LVPO-F3

LVPO-F4

CARTRIDGE	MICRON RATING	PART NO	DESCRIPTION	FLOW RATE		RATED CAPACITY		PACK SIZE	SHIP WT		LIST PRICE
				GPM	LPM	GALLONS	LITRES		LBS	KGS	
LVPO-F1	5.0	94-399-00	Removes chlorine, T&O	3.00	11.36	6,000	22,710	12	30.0	13.5	\$130.00
LVPO-F2	5.0	94-470-00	Removes sediment and scale	3.00	11.36	—	—	12	35.0	15.8	145.00
LVPO-F3	5.0	94-470-01	Removes chlorine, T&O and scale	3.00	11.36	6,000	22,710	12	38.0	17.1	151.00
LVPO-F4	—	94-470-02	Hardness removal	0.50	1.89	250	946	12	42.0	19.0	215.00

EVERPURE® GENERAL BEVERAGE AND OCS ECONOMICAL IN-LINE FILTERS

Complete line of economical in-line filters suitable for many foodservice applications. Depending on model, features include reduction of chlorine, sediment, scale, lead, and cysts. In-line UV system also available.



PRODUCT	PART NO	DESCRIPTION	FLOW RATE		RATED CAPACITY		PACK SIZE	SHIP WT		LIST PRICE
			GPM	LPM	GALLONS	LITRES		LBS	KGS	
IN-6 PG-S	EV9100-67	6" 100% phosphate for scale prevention only.	0.50	1.89	6-12 months		6	4.0	1.8	\$31.30
IN-10	EV9100-08	10" granular activated carbon with scale control.	0.80	3.03	2,400	9,080	6	6.0	2.7	31.90
IN-10	EV9100-06	10" granular activated carbon with scale control and John Guest® (JG) fittings.	0.80	3.03	2,400	9,080	6	6.0	2.7	40.50
IN-10 CS	EV9100-69	10" 100% coconut shell carbon for enhanced T&O reduction.	—	—	3,308	12,522	6	5.0	2.3	20.60
IN-10 CC	EV9100-71	10" calcite/carbon for T&O with mineral feed.	—	—	2,000	7,750	6	6.0	2.7	33.30
IN-10 NS5	EV9100-72	10" 5 micron sediment for dirt and particles.	—	—	6-12 months		6	3.0	1.4	27.20
IN-10 CK	EV9100-68	10" KDF®-55D**/carbon for T&O reduction with scale and slime prevention.	—	—	5,000	18,927	6	7.0	3.2	33.30
IN-12	EV9100-07	10" high capacity granular activated carbon with scale control.	—	—	4,800	18,168	6	7.0	3.2	40.50
IN-12	EV9100-86	10" high capacity granular activated carbon with scale control and JG fittings.	—	—	4,800	18,168	6	8.0	3.6	47.80
GAC	255599-43	GAC w/Phosphate Filter: 2" x 10"	—	—	1,350	5,110	12	10.0	4.5	25.90
CC Shell	255525-43	CC Shell Filter: 2" x 10"	—	—	3,308	12,522	12	12.0	5.4	19.50
Sediment	255579-43	Sediment Filter: 2" x 10", 5 Micron	—	—	6-12 months		12	7.0	3.2	22.00
CC Shell	255553-43	CC Shell with KDF®†† Filter: 2" x 10"	—	—	5,000	18,927	12	10.0	4.5	31.60
Clip	244454	For Standard In-Line Filters, 2.0" [5.1 cm].	—	—	—	—	1	2 oz	0.06	4.50
Clip	EV3145-50	For OCS Premium and High Capacity In-Lines, 2-1/2" [6.4 cm].	—	—	—	—	1	2 oz	0.06	2.80

*Not shown

**See individual system specification sheets for performance claims and FIFRA registration information.

†By mechanical means.

††KDF media inhibits scale buildup that can damage equipment.