

IFQ1-S SYSTEM



10.4" H x 6" W x 4" D
(264 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

IFQ1 SYSTEM



15" H x 6" W x 4" D
(381 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

IFQ2 SYSTEM



16" H x 10" W x 7.125" D
(406 mm x 254 mm x 181 mm)

Dual Cartridge with a Quick Disconnect

IFQ1-XL SYSTEM



21" H x 6" W x 4" D
(533 mm x 152 mm x 102 mm)

Single Cartridge with a Quick Disconnect

IFQ2-XL SYSTEM



23.21" H x 13" W x 4.65" D
(590 mm x 330 mm x 118 mm)

Dual Cartridge with a Quick Disconnect

IF14C & IF18C SYSTEMS



11.75" H x 2.75" W
(279 mm x 57 mm)

Filter supplied with 1/4" or 3/8" (6 or 8 mm) compression

ICE MAKING CAPACITY: Up to 600 lbs. (272 kg)
Ideal for limited-space and undercounter applications

REPLACEMENT FILTER CARTRIDGES



IOMQ-S IOMQ

Snapshot

IFQ Series water treatment systems reduce sediment down to 1/2 micron and reduce chlorine, taste and odor at a flow rate of up to 3.0. The systems include IsoNet®, which delivers consistent protection against the precipitation and accumulation of scale and provides a protective barrier to help guard against corrosion.

Features and Benefits

- Reduces maintenance frequency and cost, and extends equipment life.
- Improves equipment operating efficiency
- Incorporates IsoNet – patented scale-inhibiting technology.
- Gradient-density depth filtration reduces dirt, rust and other debris as small as 1/2 micron to ensure clean, clear ice and protect solenoids, valves and other fittings against wear and plugging.
- High-capacity activated carbon filtration reduces taste and odor and protects equipment against corrosive chlorine.
- 1/4 turn QT "Quick-Twist" cartridge makes changing the filter quick, easy and sanitary.
- Wall-mount bracket and full-flow inlet shut-off valve make installation simple.
- Certifies to NSF Standard 42

All filter systems include:

Filter cartridge with FDA approved scale inhibitor, inlet shut-off valve, gauge and quick-connect fittings.

IOMQ replacement cartridges for use with IFQ1 & IFQ2 manifold filter systems. IOMQ-XL replacement cartridge for use with IFQ1-XL manifold filter system.

IFQ SERIES FILTER SYSTEM							
Model Number	Description	Service Flow Rate Max. gpm (lpm)	Capacity Gal (L)	Operating Pressure Range Psi (bar)	Inlet Water Temp Range °F (°C)	Micron Rating	Approx. Shipping Weight lbs (kg)
IFQ1-S	Single Filter	.75 (2.84)	6,000 (22,712)	10 - 125 (0.7 - 8.6)	35 - 100 (1.7 - 38)	.5	2 (.91)
IFQ1	Single Filter	1.5 (5.68)	15,000 (56,775)				3 (1.3)
IFQ1-XL	Single Filter	2.25 (8.5)	22,500 (85,162)				5 (2.3)
IFQ2	Dual Filter	3.0 (11.4)	30,000 (113,550)				7 (3.2)
IFQ2-XL	Dual Filter	4.5 (17)	45,000 (170,344)				9 (4.1)

SINGLE INLINE FILTER CARTRIDGES						
Model Number	Description	Service Flow Rate Max. gpm (lpm)	Operating Pressure Range Psi (bar)	Inlet Water Temp Range °F (°C)	Micron Rating	Approx. Shipping Weight lbs (kg)
IF14C	Single Inline Cartridge 1/4" (6.35mm) compression	1.0 (3.79)	10 - 100 (.07 - 6.9)	35 - 100 (2 - 38)	10	2 (1)
IF18C	Single Inline Cartridge 3/8" (9.53mm) compression					

WATER FILTERS							
		IFQ1-S	IFQ1	IFQ1-XL	IFQ2	IFQ2-XL	IF14C IF18C
CUBE ICE	ICEU070	X					X
	ICEU150 - ICEU220 - ICEU300	X					X
	CIMO320 - CIMO430		X				
	CIMO520 - CIMO630			X			
	CIMO826 - CIM1136				X		
	CIM1446 - CIM1545				X		
	CIM1845 - CIM2046					X	
	ICE1506 - MODULAR				X		
FLAKE ICE	UCGO60 - UCG130*	X					X
	MFI0500	X					X
	MFI0800 - MFI1256			X			
	MFI1506				X		
PEARL ICE	MFI2306					X	
	GEMU090	X					X
	GEMO450 - GEMO650		X				
	GEMO956			X			
	GEM1306				X		
	GEM2006					X	

* Gourmet Ice

Installation Tips

- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for cartridge removal and replacement.
- Connect filtered water line to ice connections only. Do not use for condenser water.
- No activation procedure or flushing is required for system to perform as specified.

Extended Warranty Program

- Buy a new Ice-O-Matic Water Filter System with a new CIM Series™ Cube ice maker, replace the filter cartridge every 6 months, and Ice-O-Matic will extend the limited cuber evaporator warranty to 7 years parts and labor (U.S. and Canada only).
- New ice maker and filter must be installed at the same time.
- Ice maker and water filter must be registered with Ice-O-Matic within 10 days of installation. Register ice maker and filter at Iceomatic.com/warranty.
- Water filters must be changed every 180 days (6 months), at a minimum. All changes must be registered with Ice-O-Matic and include the water filter's model and serial numbers. Register water filter changes at www.iceomatic.com.
- Program is available with all Ice-O-Matic IFQ1-S, IFQ1, IFQ1-XL, IFQ2, IFQ2-XL, IF14C or IF18C water filter systems.
- Replacement filter must be Ice-O-Matic models.